

	Specification	Symbol	Condition / Comment	1001-40-LC2	1201-40 LC2	1401-40 LC2	Unit	
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 40 \mu ADC$, $T_{case} = 70^{\circ}C$	± 100	± 120	± 140	kVDC	
	Maximum Isolation Voltage	V_i	Between HV switch and control / GND, continuously			± 180	kVDC	
	Max. Housing Insulation Voltage	V_{INS}	Between switch and housing surface, 3 minutes			± 200	kVDC	
	Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$ $t_p < 200 \mu s$, duty cycle $< 1\%$ $t_p < 1 ms$, duty cycle $< 1\%$ $t_p < 10 ms$, duty cycle $< 1\%$ $t_p < 100 ms$, duty cycle $< 1\%$		400 236 114 275		ADC	
	Maximum Continuous Load Current	$I_{L(max)}$	$T_{case} = 25^{\circ}C$ Standard devices Devices with option DLC		3.4 30		ADC	
	Max. Continuous Power Dissipation	$P_{d(max)}$	$T_{case} = 25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	120 3000	150 3200	160 3300	Watt	
	Linear Derating		Above $25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	2.84 237,5	3.4 307,31	3.72 354,81	W/K	
	Operating Temperature Range	T_o	Standard devices & options CF, GCF, ILC. (Option DLC)			$-40...70 (60)$		$^{\circ}C$
	Storage Temperature Range	T_s	Switches with option ILC may require frost protection!			$-40...90$		$^{\circ}C$
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch			25		mT
	Max. Auxiliary Voltage	V_{aux}	Built-in overvoltage limiter (replaceable)			5.5		VDC
ELECTRICAL CHARACTERISTICS	Permissible Operating Voltage Range	V_o		$0... \pm 100$	$0... \pm 120$	$0... \pm 140$	kVDC	
	Typical Breakdown Voltage	V_{br}	NOTE: V_{br} is a test parameter for quality control purposes only. Not applicable in normal operation! $I_{off} > 0.5 mA$	110	132	148	kVDC	
	Typical Off-State Current	I_{off}	$0.8 \times V_o$, $T_{case} = 25...70^{\circ}C$, reduced I_{off} on request		< 40		μADC	
	Typical Turn-On Resistance	R_{stat}	Each switching path $t_p < 1 \mu s$, duty cycle $< 1\%$	$0.1 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 70^{\circ}C$	10 20 49.7	21 41.6 103.7	13 51.6 129.8	Ohm
	Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$, $0.8 \times V_{O(max)}$, 50-50%		250		ns	
	Typical Output Pulse Jitter	t_j	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$		3		ns	
	Typical Turn-On Rise Time	$t_{r(on)}$	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	50 95 101	55 98 108	60 103 114	ns
	Typical Turn-Off Rise Time	t_{off}, t_q	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	50 100		ns	
	Maximum Turn-On Time	$t_{on(max)}$	No limitation		∞		ns	
	Minimum Turn-On Time	$t_{on(min)}$	$t_{on(min)}$ can be customized. Please consult factory		250		ns	
	Maximum Turn-Off Time	$t_{off(max)}$	No limitation		∞		ns	
	Minimum Turn-Off Time	$t_{off(min)}$	$t_{off(min)}$ can be customized. Please consult factory		250		ns	
	Max. Continuous Switching Frequency	$f_{(max)}$	@ $V_{aux} = 5.00 V$ Sw. shutdown if $f_{(max)}$ is exceeded	Standard devices without HFS option Standard devices with HFS supply Opt. HFS + sufficient cooling option	< 1.0 40 70		kHz	
	Maximum Burst Frequency	$f_b(max)$	Use option HFB for > 10 pulses within 20 μs or less		500		MHz	
	Maximum Number of Pulses / Burst	$N_{(max)}$	@ $f_b(max)$ Note: Option HFB requires external buffer capacitors with a voltage rating of $> 630VDC$ and a capacitance of 100nF per additional pulse	Standard Option I-HFB Option HFB	> 10 > 100 > 1000		Pulses	
	Coupling Capacitance	C_C	HV side against control side		< 100		pF	
	Natural Capacitance	C_N	Between switch poles, @ $0.5 \times V_{O(max)}$		10... 5		pF	
	Control Voltage Range	V_{ctrl}	The V_{ctrl} has no impact on the output pulse shape.		3 ... 10		VDC	
	Auxiliary Supply Voltage Range	V_{aux}	The +5 V supply is not required in the HFS mode.		4.5 ... 5.5		VDC	
	Typical Auxiliary Supply Current	I_{aux}	$V_{aux} = 5.00 VDC$, $T_{case} = 25^{\circ}C$. Active current limitation above 1A.	$0.01 \times f_{(max)}$ @ $f_{(max)}$	400 800		mADC	
	Fault Signal Output		Switch will be turn off, if $f > f_{(max)}$, $V_{aux} < 4.75V$ or $T_{case} > 75^{\circ}C$ Fault condition is indicated by a logical "L"		> 4.0 < 0.8		VDC	
	Opt. HFS, Ext. Supply Voltage V1	$V_{HFS(V1)}$	Stability $\pm 3\%$, current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$		15		VDC	
	Opt. HFS, Ext. Supply Voltage V2	$V_{HFS(V2)}$	Stability $\pm 3\%$, current consumption $< 0.5 mA/kHz$ @ $25^{\circ}C$		TBD		VDC	
	Intrinsic Diode Forward Voltage	V_F	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$		100	109	118	VDC
	Diode Reverse Recovery Time	t_{rrc}	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$, $di/dt = 100 A/\mu s$		$< 250ns$		ns	
HOUSING	Dimensions	LxWxH	Standard housing Devices with option DLC	Please contact the manufacturer!			mm ³	
	Weight		Standard housing Devices with option DLC	Please contact the manufacturer!			Kg	
FUNCTIONS	Control Signal Input	Pin 1 / Yellow (LS-C: Pin 1). TTL compatible (LS-C: With 100 Ω termination). Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V for low jitter).						
	Logic GND / 5V Return	Pin 2 / Black (LS-C: Shielding). The ground pin is internally connected with the safety earthings terminals (threaded inserts) on bottom side.						
ORDERING	5V Auxiliary Supply	Pin 3 / Red (LS-C: Pin 4). The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$. Higher rep rates require option HFS.						
	Fault Signal Output	Pin 4 / Orange (LS-C: Pin 3). TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault.						
	Inhibit Signal Input	Pin 5 / Green (LS-C: Pin 2). TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited.						
	LED Indicators	GREEN: "Auxiliary power good, switch OFF". YELLOW: "Control signal received, switch ON". RED: "Fault condition, switch OFF"						
	Temperature Protection	Switches with option DLC: $65^{\circ}C$, response time $< 3 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (40 to $65^{\circ}C$), coolant flow $> 3 l / min$. Separate driver protection.						
	HTS 1001-40-LC2	Fast HV Mosfet Switch, 100kV, 400 A	Option LP	Low Pass. Input filter for increased noise immunity.	Option I-PC	Integrated part components according to customer specification.		
	HTS 1201-40-LC2	Fast HV Mosfet Switch, 120kV, 400 A	Option HFB	High Frequency Burst (improved capability by external capacitors)	Option UL-94	Flame retardant casting resin, UL94-V0		
HTS 1401-40-LC2	Fast HV Mosfet Switch, 140kV, 400 A	Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2)	Option I-FWD	Integrated Free-Wheeling Diode. In connection with inductive load only.			
		Option I-HFS	Integrated High Frequency Burst	Option I-FWDN	Integrated Freewheeling Diode Network. In connection with inductive load.			
		Option S-TT	Soft Transition Time decrease the rise and fall time by 20%	Option PT-C	Pigtail for control connection: Flexible leads (l=75mm) with lemo			
		Option Min-On	Individually increased "Min. On-Time" to avoid unwanted triggering	Option SEP-C	Separated control unit. Control unit with LED indicators in a separate			
		Option Min-Off	Individually increased "Min. Off-Time" to avoid unwanted triggering	Option TH	Tubular Housing			
		Option PCC	Pulser Configuration. Switch combined with custom specific parts.	Option CF	Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.			
		Option ISO-120	120kV Isolation. Isolation Voltage increased to 120kV.	Option DLC	Direct Liquid Cooling. $P_{d(max)}$ can be increased by the factor 10 to 100.			
		Option ISO-200	200kV Isolation. Isolation Voltage increased to 200kV.	FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.				
		Customized switching units are available on request. All data and specifications subject to change without notice. Please visit www.behlke.com for up-dates.				1001-40-LC2-RS / Revision 13-01-2019 ©2012 All rights		