

	Specification	Symbol		HTS 121-120 SiC	Unit
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 80 \mu ADC$, $T_{case} = 70^{\circ}C$	± 12	kVDC
	Maximum Isolation Voltage	V_i	Between HV switch and control / GND, continuously	± 25	kVDC
	Max. Housing Insulation Voltage	V_{INS}	Between switch and housing surface, 3 minutes	± 50	kVDC
	Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$ $t_p < 200 \mu s$, duty cycle $< 1\%$ $t_p < 1 ms$, duty cycle $< 1\%$ $t_p < 10 ms$, duty cycle $< 1\%$ $t_p < 100 ms$, duty cycle $< 1\%$	1200 760 230 120	ADC
	Maximum Continuous Load Current	$I_{L(max)}$	$T_{case} = 25^{\circ}C$ Standard devices Devices with option GCF Devices with option DLC	10 60 100	ADC
	Max. Continuous Power Dissipation	$P_{d(max)}$	$T_{case} = 25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	34 3000	Watt
	Linear Derating		Above $25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	0.12 80	W/K
	Operating Temperature Range	T_o	Standard devices & options CF, GCF, ILC. (Option DLC)	-40...75	$^{\circ}C$
	Storage Temperature Range	T_s	Switches with option ILC may require frost protection!	-50...90	$^{\circ}C$
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch	25	mT
ELECTRICAL CHARACTERISTICS	Max. Auxiliary Voltage	V_{aux}	Built-in overvoltage limiter (replaceable)	5	VDC
	Permissible Operating Voltage Range	V_o		$0 \dots \pm 12$	kVDC
	Typical Breakdown Voltage	V_{br}	NOTE: V_{br} is a test parameter for quality control purposes only. Not applicable in $I_{off} > 0.5 mA$	13	kVDC
	Typical Off-State Current	I_{off}	$0.8 \times V_o$, $T_{case} = 25 \dots 70^{\circ}C$, reduced I_{off} on request	< 80	μADC
	Typical Turn-On Resistance	R_{stat}	Each switching path $t_p < 1 \mu s$, duty cycle $< 1\%$ $0.1 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 70^{\circ}C$	0.06 0.12 0.25	Ohm
	Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$, $0.8 \times V_{O(max)}$, 50-50%	200	ns
	Typical Output Pulse Jitter	t_j	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$	3	ns
	Typical Turn-On/Off Rise Time	$t_{r(on)}/t_{r(off)}$	Resistive load, 10-90% $0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	28 50 60	ns
	Maximum Turn-On Time	$t_{on(max)}$	No limitation	∞	
	Minimum Turn-On Time	$t_{on(min)}$	$t_{on(min)}$ can be customized. Please consult factory	150	ns
	Maximum Turn-Off Time	$t_{off(max)}$	No limitation	∞	
	Minimum Turn-Off Time	$t_{off(min)}$	$t_{off(min)}$ can be customized. Please consult factory	150	ns
	Max. Continuous Switching Frequency	$f_{(max)}$	@ $V_{aux} = 5.00 V$ Sw. shutdown if $f_{(max)}$ is exceeded Standard devices without HFS option Standard devices with HFS supply Opt. HFS + sufficient cooling option	TBD 25 100	kHz
	Maximum Burst Frequency	$f_{b(max)}$	Use option HFB for > 10 pulses within 20 μs or less	500	kHz
	Maximum Number of Pulses / Burst	$N_{(max)}$	@ $f_{b(max)}$ Note: Option HFB requires external buffer capacitors with a voltage rating of $> 630 VDC$ and a capacitance of 100nF per additional pulse Standard Option I-HFB Option HFB	> 10 Use option HFB for > 10 > 100 > 1000	Pulses
	Coupling Capacitance	C_c	HV side against control side	< 100	pF
	Natural Capacitance	C_n	Between switch poles, @ $0.5 \times V_{O(max)}$	< 50	pF
	Control Voltage Range	V_{ctrl}	The V_{ctrl} has no impact on the output pulse shape.	3... 10	VDC
	Auxiliary Supply Voltage Range	V_{aux}	The +5 V supply is not required in the HFS mode.	5	VDC
	Typical Auxiliary Supply Current	I_{aux}	$V_{aux} = 5.00 VDC$, $T_{case} = 25^{\circ}C$. Active current limitation above 1A. $0.01 \times f_{(max)}$ @ $f_{(max)}$	> 150 800	mADC
	Fault Signal Output		Switch will be turn off, if $f > f_{(max)}$, $V_{aux} < 4.75V$ or $T_{case} > 75^{\circ}C$ Fault condition is indicated by a logical "L"	H=4V, L=0.5V	VDC
	Opt. HFS, Ext. Supply Voltage V1	$V_{HFS(V1)}$	Stability $\pm 3\%$, current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$	15	VDC
	Opt. HFS, Ext. Supply Voltage V2	$V_{HFS(V2)}$	Stability $\pm 3\%$, current consumption $< 0.9 mA/kHz$ @ $25^{\circ}C$	TBD	VDC
	Intrinsic Diode Forward Voltage	V_f	$T_{case} = 25^{\circ}C$, $I_f = 0.3 \times I_{P(max)}$	< 30	VDC
	Diode Reverse Recovery Time	t_{rrc}	$T_{case} = 25^{\circ}C$, $I_f = 0.3 \times I_{P(max)}$, $di/dt = 100 A/\mu s$	< 250	ns
HOUSING	Dimensions	LxWxH	Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC	Please contact the manufacturer!	mm ³
	Weight		Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC	Please contact the manufacturer!	g
FUNCTIONS	Control Signal Input	Pin 1 / Yellow. TTL compatible with Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V recommended for low jitter). Pin 2 / Black. The ground pin is internally connected with the safety earthing terminal (threaded insert) on bottom side. Pin 3 / Red. The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$. Higher rep rates require option HFS. Pin 4 / Orange. TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault. Pin 5 / Green. TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited. GREEN: "Auxiliary power good, switch OFF". YELLOW: "Control signal received, switch ON". RED: "Fault condition, switch OFF" A) Standard switches and switches with option CF, GCF: Thermo trigger $75^{\circ}C$, response time $< 60 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (50 to $75^{\circ}C$). Separate driver protection. B) Switches with option DLC: $65^{\circ}C$, response time $< 3 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (40 to $65^{\circ}C$), coolant flow $> 3 l / min$. Separate driver protection.			
	Logic GND / 5V Return				
	5V Auxiliary Supply				
	Fault Signal Output				
	Inhibit Signal Input				
	LED Indicators				
	Temperature Protection				
ORDERING TI	HTS 121-120 SiC	Transistor Switch, 12 kVDC, 1200ADC	Option LP Low Pass. Input filter for increased noise immunity.	Option CCS Ceramic Cooling Surface. $P_{d(max)}$ can be increased by the factor 2 to 3.	
			Option S-TT Soft Transition Time. Slower switching speed for simplified EMC.	Option CCF Ceramic Flange Housing. $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option HFB High Frequency Burst. Improved burst capability by driver.	Option CF Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.	
			Option HFS High Frequency Switching (two auxiliary supply inputs V1 & V2)	Option GCF Grounded Cooling Flange (copper). $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option UFTR Ultra Fast Thermotrigger. Response time for shut down $< 5s$.	Option ILC Indirect Liquid Cooling (for water). $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option UFTS Ultra Fast Thermosensor. Response time $< 5s$. NTC $10k / \pm 1\%$	Option DLC Direct Liquid Cooling (for FPE/PFC). $P_{d(max)}$ can be increased by the factor 10 to 100.	
			FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.		