

	Specification	Symbol	Condition / Comment		151-180-SiC	Unit
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 80 \mu ADC$, $T_{case} = 70^{\circ}C$		± 15	kVDC
	Maximum Isolation Voltage	V_i	Between HV switch and control / GND, continuously		± 25	kVDC
	Max. Housing Insulation Voltage	V_{INS}	Between switch and housing surface, 3 minutes		± 50	kVDC
	Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$	$t_p < 200 \mu s$, duty cycle $< 1\%$ $t_p < 1 ms$, duty cycle $< 1\%$ $t_p < 10 ms$, duty cycle $< 1\%$ $t_p < 100 ms$, duty cycle $< 1\%$	1800 1000 340 120	ADC
	Maximum Continuous Load Current	$I_{L(max)}$	$T_{case} = 25^{\circ}C$	Standard devices Devices with option DLC	7 50	ADC
	Max. Continuous Power Dissipation	$P_{d(max)}$	$T_{case} = 25^{\circ}C$	Standard devices & FC, forced air 4 m/s Devices with option ILC	70 1200	Watt
	Linear Derating		Above $25^{\circ}C$	Standard devices & FC, forced air 4 m/s Devices with option DLC	0.2 150	W/K
	Operating Temperature Range	T_o	Standard devices & options CF, GCF, ILC. (Option DLC)		-40...70 (60)	$^{\circ}C$
	Storage Temperature Range	T_s	Switches with option ILC may require frost protection!		-40...90	$^{\circ}C$
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch		25	mT
Max. Auxiliary Voltage	V_{aux}	Built-in overvoltage limiter (replaceable)		5.5	VDC	
ELECTRICAL CHARACTERISTICS	Permissible Operating Voltage Range	V_o			$0... \pm 15$	kVDC
	Typical Breakdown Voltage	V_{br}	NOTE: V_{br} is a test parameter for quality control purposes only. Not applicable in normal operation!	$I_{off} > 0.5 mA$	16	kVDC
	Typical Off-State Current	I_{off}	$0.8 \times V_o$, $T_{case} = 25...70^{\circ}C$, reduced I_{off} on request		< 80	μADC
	Typical Turn-On Resistance	R_{stat}	Each switching path $t_p < 1 \mu s$, duty cycle $< 1\%$	$0.1 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 70^{\circ}C$	0.047 0.09 0.2	Ohm
	Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$, $0.8 \times V_{O(max)}$, 50-50%		200	ns
	Typical Output Pulse Jitter	t_j	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$		3	ns
	Typical Turn-On Rise Time	$t_{r(on)}$	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	TBD TBD TBD	ns
	Typical Turn-Off Rise Time	t_{off}, t_q	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	50 100	ns
	Maximum Turn-On Time	$t_{on(max)}$	No limitation		∞	ns
	Minimum Turn-On Time	$t_{on(min)}$	$t_{on(min)}$ can be customized. Please consult factory		200	ns
	Maximum Turn-Off Time	$t_{off(max)}$	No limitation		∞	ns
	Minimum Turn-Off Time	$t_{off(min)}$	$t_{off(min)}$ can be customized. Please consult factory		200	ns
	Max. Continuous Switching Frequency	$f_{(max)}$	@ $V_{aux} = 5.00 V$ Sw. shutdown if $f_{(max)}$ is exceeded	Standard devices without HFS option Standard devices with HFS supply Opt. HFS + ILC	TBD 80 150	kHz
	Maximum Burst Frequency	$f_b(max)$	Use option HFB for > 10 pulses within $20 \mu s$ or less		500	kHz
	Maximum Number of Pulses / Burst	$N_{(max)}$	@ $f_b(max)$ Note: Option HFB requires external buffer capacitors with a voltage rating of $> 630VDC$ and a capacitance of 100nF per additional pulse	Standard Option I-HFB Option HFB	> 10 > 100 > 1000	Pulses
	Coupling Capacitance	C_C	HV side against control side		< 100	pF
	Natural Capacitance	C_N	Between switch poles, @ $0.5 \times V_{O(max)}$		200	pF
	Control Voltage Range	V_{ctrl}	The V_{ctrl} has no impact on the output pulse shape.		3 ... 10	VDC
	Auxiliary Supply Voltage Range	V_{aux}	The +5 V supply is not required in the HFS mode.		4.5 ... 5.5	VDC
	Typical Auxiliary Supply Current	I_{aux}	$V_{aux} = 5.00 VDC$, $T_{case} = 25^{\circ}C$. Active current limitation above 1A.	$0.01 \times f_{(max)}$ @ $f_{(max)}$	TBD 800	mADC
	Fault Signal Output		Switch will be turn off, if $f > f_{(max)}$, $V_{aux} < 4.75V$ or $T_{case} > 75^{\circ}C$ Fault condition is indicated by a logical "L"		> 4.0 < 0.8	VDC
	Opt. HFS, Ext. Supply Voltage V1	$V_{HFS(V1)}$	Stability $\pm 3\%$, current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$		15	VDC
	Opt. HFS, Ext. Supply Voltage V2	$V_{HFS(V2)}$	Stability $\pm 3\%$, current consumption $< 0.5 mA/kHz$ @ $25^{\circ}C$		TBD	VDC
	Intrinsic Diode Forward Voltage	V_F	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$		TBD	VDC
	Diode Reverse Recovery Time	t_{rrc}	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$, $di/dt = 100 A/\mu s$		$< 50ns$	ns
HOUSING	Dimensions	LxWxH	Standard housing Devices with option ILC		Please contact the manufacturer!	mm ³
	Weight		Standard housing		Please contact the manufacturer!	g
FUNCTIONS	Control Signal Input Logic GND / 5V Return 5V Auxiliary Supply Fault Signal Output Inhibit Signal Input LED Indicators Temperature Protection	Pin 1 / Yellow (LS-C: Pin 1). TTL compatible (LS-C: With 100Ω termination). Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V for low jitter). Pin 2 / Black (LS-C: Shielding). The ground pin is internally connected with the safety earthings terminals (threaded inserts) on bottom side. Pin 3 / Red (LS-C: Pin 4). The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$. Higher rep rates require option HFS. Pin 4 / Orange (LS-C: Pin 3). TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault. Pin 5 / Green (LS-C: Pin 2). TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited. GREEN: "Auxiliary power good, switch OFF". YELLOW: "Control signal received, switch ON". RED: "Fault condition, switch OFF" Switches with option DLC: $65^{\circ}C$, response time $< 3 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (40 to $65^{\circ}C$), coolant flow $> 3 l / min$. Separate driver protection.				
ORDERING	HTS 151-180-SiC	Fast HV SiC Mosfet Switch, 15kV, 1800	Option LP	Low Pass. Input filter for increased noise immunity.	Option I-PC	Integrated part components according to customer specification.
			Option HFB	High Frequency Burst (improved capability by external capacitors)	Option UL-94	Flame retardant casting resin, UL94-V0
			Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2)	Option I-FWD	Integrated Free-Wheeling Diode. In connection with inductive load only.
			Option I-HFS	Integrated High Frequency Burst	Option I-FWDN	Integrated Freewheeling Diode Network. In connection with inductive load.
			Option S-TT	Soft Transition Time decrease the rise and fall time by 20%	Option PT-C	Pigtail for control connection: Flexible leads (l=75mm) with lemo
			Option Min-On	Individually increased "Min. On-Time" to avoid unwanted triggering	Option SEP-C	Separated control unit. Control unit with LED indicators in a separate
			Option Min-Off	Individually increased "Min. Off-Time" to avoid unwanted triggering	Option TH	Tubular Housing
			Option PCC	Pulser Configuration. Switch combined with custom specific parts.	Option CF	Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.
			Option ISO-40	40kV Isolation. Isolation Voltage increased to 120kV.	Option DLC	Direct Liquid Cooling. $P_{d(max)}$ can be increased by the factor 10 to 100.
			Option ISO-60	60kV Isolation. Isolation Voltage increased to 200kV.	FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.	
Customized switching units are available on request. All data and specifications subject to change without notice. Please visit www.behlke.com for up-dates.						