

	Specification	Symbol	Condition / Comment	21-03-GSM	81-03-GSM	161-03-GSM	Unit	
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 40 \mu ADC$ , $T_{case} = 70^{\circ}C$		$\pm 2$	$\pm 8$	$\pm 16$	kVDC
	Maximum Isolation Voltage	$V_I$	Between HV switch and control / GND, continuously			$\pm 25$		kVDC
	Max. Housing Insulation Voltage	$V_{INS}$	Between switch and housing surface, 3 minutes			$\pm 30$		kVDC
	Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$	$t_p < 10 \mu s$ , duty cycle $< 1\%$ $t_p < 1 ms$ , duty cycle $< 1\%$ $t_p < 10 ms$ , duty cycle $< 1\%$ $t_p < 100 ms$ , duty cycle $< 1\%$		30 17 10 7		ADC
	Maximum Continuous Load Current	$I_{L(max)}$	$T_{case} = 25^{\circ}C$	Standard devices Devices with option CF, forced air 4 m/s Devices with option DLC		0.33 1.29 1.49		ADC
	Max. Continuous Power Dissipation	$P_{d(max)}$	$T_{case} = 25^{\circ}C$	Standard devices & FC, forced air 4 m/s Devices with option CF, forced air 4 m/s Devices with option DLC	10 150 1100	12 180 1500	20 300 1600	Watt
	Linear Derating		Above $25^{\circ}C$	Standard devices & FC, forced air 4 m/s Devices with option CF, forced air 4 m/s Devices with option DLC	0.22 3.33 20.44	0,26 4,00 30.33	0,44 6,66 35.55	W/K
	Operating Temperature Range	$T_O$	Standard devices & options CF, GCF, ILC. (Option DLC)		-40...70 (60)			$^{\circ}C$
	Storage Temperature Range	$T_S$	Switches with option ILC may require frost protection!		-40...90			$^{\circ}C$
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch		25			mT
Max. Auxilliary Voltage	$V_{aux}$	Built-in overvoltage limiter (replaceable)		5.5			VDC	
ELECTRICAL CHARACTERISTICS	Permissible Operating Voltage Range	$V_O$	Unipolar operation (one switch pole grounded or floated) Bipolar operation (positive & negative voltage applied)		0... $\pm 2$ 0... $\pm 1$	0... $\pm 8$ 0... $\pm 4$	0... $\pm 16$ 0... $\pm 8$	kVDC
	Typical Breakdown Voltage	$V_{br}$	NOTE: $V_{br}$ is a test parameter for quality control purposes only. Not applicable in normal operation! $I_{off} > 0.5 mA$		2.20	8.80	17.60	kVDC
	Typical Off-State Current	$I_{off}$	$0.8 \times V_O$ , $T_{case} = 25...70^{\circ}C$ , reduced $I_{off}$ on request		$< 40$			$\mu ADC$
	Typical Turn-On Resistance	$R_{stat}$	Each switching path $t_p < 1 \mu s$ , duty cycle $< 1\%$	$0.1 \times I_{P(max)}$ , $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$ , $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$ , $T_{case} = 70^{\circ}C$	3.8 7.6 15.2	16 36 78	32 76 172	Ohm
	Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$ , $0.8 \times V_{O(max)}$ , 50-50%		250			ns
	Typical Output Pulse Jitter	$t_j$	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$		3			ns
	Typical Ouput Transition Time (Rise Time & Fall Time)	$t_r, t_f$	Resistive load, 10-90%	$0.1 \times V_{O(max)}$ , $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$ , $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$ , $I_L = 1.0 \times I_{P(max)}$	15 39 45	15 37 44	16 44 48	ns
	Maximum Turn-On Time	$t_{on(max)}$	No limitation		$\infty$			ns
	Minimum Turn-On Time	$t_{on(min)}$	can be customized. Please consult factory		150			ns
	Max. Continuous Switching Frequency	$f_{(max)}$	@ $V_{aux} = 5.00 V$ Sw. shutdown if $f_{(max)}$ is exceeded	Standard devices without HFS option Standard devices with HFS supply Opt. HFS + sufficient cooling option	25 50 100	12 50 100	5 50 100	kHz
	Maximum Burst Frequency	$f_{b(max)}$	Use option HFB for $> 10$ pulses within $20 \mu s$ or less		1			MHz
	Maximum Number of Pulses / Burst	$N_{(max)}$	$f_b = 1 MHz$ (1 $\mu s$ spacing). Switch shutdown if $N_{(max)}$ is exceeded.		20 Use burst option HFB for $> 20$ pulses			Pulses
	Coupling Capacitance	$C_C$	Switch against control side	Standard devices & options CF, DLC Devices with options GCF, ILC	$< 50$ 70 ... 200			pF
	Natural Capacitance	$C_N$	Between switch poles, @ $0.5 \times V_{O(max)}$		$< 50$			pF
	Control Voltage Range	$V_{ctrl}$	The $V_{ctrl}$ has no impact on the output pulse shape.		3 ... 10			VDC
	Auxiliary Supply Voltage Range	$V_{aux}$	The +5 V supply is not required in the HFS mode.		4.5 ... 5.5			VDC
	Typical Auxiliary Supply Current	$I_{aux}$	$V_{aux} = 5.00 VDC$ , $T_{case} = 25^{\circ}C$ . Active current limitation above 1A.	$0.01 \times f_{(max)}$ @ specified $f_{(max)}$	150 800	210 800	270 800	mADC
	Opt. HFS, Ext. Supply Voltage V1	$V_{HFS(V1)}$	Stability $\pm 3\%$ , current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$		15			VDC
	Opt. HFS, Ext. Supply Voltage V2	$V_{HFS(V2)}$	Stability $\pm 3\%$ , current consumption $< 0.5 mA/kHz$ @ $25^{\circ}C$		210			VDC
	Intrinsic Diode Forward Voltage	$V_F$	$T_{case} = 25^{\circ}C$ , $I_F = 0.3 \times I_{P(max)}$		14			VDC
	Diode Reverse Recovery Time	$t_{rrc}$	$T_{case} = 25^{\circ}C$ , $I_F = 0.3 \times I_{P(max)}$ , $di/dt = 100 A/\mu s$		$< 500 ns$			ns
	HOUSING	Dimensions	LxWxH	Standard housing, without pigtails Devices with option CF Devices with option ILC & DLC	Please consult BEHLKE!			mm <sup>3</sup>
Weight			Standard housing Devices with option CF Devices with option ILC & DLC	Please consult BEHLKE!			g	
FUNCTIONS	Control Signal Input	<b>Pin 1 / Yellow (LS-C: Pin 1).</b> TTL compatible (LS-C: With 100 $\Omega$ termination). Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V for low jitter). <b>Pin 2 / Black (LS-C: Shielding).</b> The ground pin is internally connected with the safety earthing terminals (threaded inserts) on bottom side. <b>Pin 3 / Red (LS-C: Pin 4).</b> The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$ . Higher rep rates require option HFS. <b>Pin 4 / Orange (LS-C: Pin 3).</b> TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault. <b>Pin 5 / Green (LS-C: Pin 2).</b> TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited. <b>GREEN:</b> "Auxiliary power good, switch OFF". <b>YELLOW:</b> "Control signal received, switch ON". <b>RED:</b> "Fault condition, switch OFF" <b>A)</b> Standard switches and switches with opt. FC, CF, GCF: Thermo trigger $75^{\circ}C$ , response time $< 60 s$ @ $3 \times P_d(max)$ , $\Delta T = 25K$ (50 to $75^{\circ}C$ ). Separate driver protection. <b>B)</b> Switches with option DLC: $65^{\circ}C$ , response time $< 3 s$ @ $3 \times P_d(max)$ , $\Delta T = 25K$ (40 to $65^{\circ}C$ ), coolant flow $> 3 l/min$ . Separate driver protection.						
	Logic GND / 5V Return							
	5V Auxiliary Supply							
	Fault Signal Output							
	Inhibit Signal Input							
	LED Indicators							
	Temperature Protection							
ORDERING	HTS 21-03-GSM	Fast HV Push-Pull Switch, 2kV, 30 A	Option LP	Low Pass. Input filter for increased noise immunity.	Option I-PC	Integrated part components according to customer specification.		
	HTS 81-03-GSM	Fast HV Push-Pull Switch, 8kV, 30 A	Option HFB	High Frequency Burst (improved capability by external capacitors)	Option UL-94	Flame retardant casting resin, UL94-V0		
	HTS 161-03-GSM	Fast HV Push-Pull Switch, 16kV, 30 A	Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2 )	Option I-FWD	Integrated Free-Wheeling Diode. In connection with inductive load only.		
			Option I-HFS	Integrated High Frequency Burst	Option I-FWDN	Integrated Free-wheeling Diode Network. In connection with inductive load.		
			Option S-TT	Soft Transition Time decrease the rise and fall time by 20%	Option PT-C	Pigtail for control connection: Flexible leads (l=75mm) with lermo connector.		
			Option Min-On	Individually increased "Min. On-Time" to avoid unwanted triggering	Option SEP-C	Separated control unit. Control unit with LED indicators in a separate		
			Option Min-Off	Individually increased "Min. Off-Time" to avoid unwanted triggering	Option TH	Tubular Housing		
			Option PCC	Pulser Configuration. Switch combined with custom specific parts.	Option CF	Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.		
			Option ISO-40	40kV Isolation. Isolation Voltage increased to 40kV.	Option GCF	Grounded Cooling Flange. $P_{d(max)}$ can be increased by the factor 3 to 15.		
			Option ISO-80	80kV Isolation. Isolation Voltage increased to 80kV.	Option ILC	Indirect Liquid Cooling (for water). $P_{d(max)}$ can be increased by the factor 3 to 15.		
			Option ISO-120	120kV Isolation. Isolation Voltage increased to 120kV.	Option DLC	Direct Liquid Cooling. $P_{d(max)}$ can be increased by the factor 10 to 100.		
			Option ISO-200	200kV Isolation. Isolation Voltage increased to 200kV.	FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.			
		For further orderings options please refer to our on-line catalog, section C8. <a href="https://www.behlke.com/separations/separation_c8.htm">https://www.behlke.com/separations/separation_c8.htm</a>		Customized switching units are available on request. All data and specifications subject to change without notice. Please visit <a href="http://www.behlke.com">www.behlke.com</a> for up-dates.				
						21-03-GSM-RS / Revision 21-07-2018 ©2012 All rights reserved		