







|                            | Specification  | Symbol  | Condition / Comment  | 21-06 GSM  | Unit         |  |                           |
|----------------------------|--|---|--|--|--------------|--|---------------------------|
| ABSOLUTE MAXIMUM RATINGS   | Maximum Operating Voltage  | V <sub>O(max)</sub>   | I <sub>off</sub> < 10 μADC, T <sub>case</sub> = 70°C   | 2  | kVDC         |  |                           |
|                            | Maximum Isolation Voltage  | V <sub>I</sub>  | Between HV switch and control / GND, continuously  | 10   | kVDC         |  |                           |
|                            | Max. Housing Insulation Voltage  | V <sub>INS</sub>  | Between switch and housing surface, 3 minutes  | 10   | kVDC         |  |                           |
|                            | Maximum Turn-On Peak Current   | I <sub>P(max)</sub>   | T <sub>case</sub> = 25°C<br>t <sub>p</sub> < 200 μs, duty cycle <1%<br>t <sub>p</sub> < 1 ms, duty cycle <1%<br>t <sub>p</sub> < 10 ms, duty cycle <1%<br>t <sub>p</sub> < 100 ms, duty cycle <1%  | 60<br>32<br>18<br>5  | ADC          |  |                           |
|                            | Maximum Continuous Load Current  | I <sub>L(max)</sub>   | T <sub>case</sub> = 25°C<br>Standard devices<br>Option CF, cooling fins<br>Devices with option DLC   | 0.91<br>2.01<br>4.82   | ADC          |  |                           |
|                            | Max. Continuous Power Dissipation  | P <sub>d(max)</sub>   | T <sub>case</sub> = 25°C<br>Standard devices & FC, forced air 4 m/s<br>Devices with option DLC   | 10<br>1000   | Watt         |  |                           |
|                            | Linear Derating  |   | Above 25°C<br>Standard devices & FC, forced air 4 m/s<br>Devices with option DLC   | 0.22<br>20   | W/K          |  |                           |
|                            | Operating Temperature Range  | T <sub>O</sub>  | Standard devices & options ILC, DLC  | -40...70 (60)  | °C           |  |                           |
|                            | Storage Temperature Range  | T <sub>S</sub>  | Switches with option ILC may require frost protection!   | -40...90   | °C           |  |                           |
|                            | Max. Permissible Magnetic Field  | B   | Homogeneous steady-field, surrounding the whole switch   | 25   | mT           |  |                           |
| Max. Auxilliary Voltage    | V <sub>aux</sub>   | Built-in overvoltage limiter (replaceable)  | 5.5  | VDC  |              |  |                           |
| ELECTRICAL CHARACTERISTICS | Permissible Operating Voltage Range  | V <sub>O</sub>  | Unipolar operation (one switch pole grounded or floated)<br>Bipolar operation (positive & negative voltage applied)  | 0... ± 2<br>0... ± 1   | kVDC         |  |                           |
|                            | Typical Breakdown Voltage  | V <sub>br</sub>   | NOTE: V <sub>br</sub> is a test parameter for quality control purposes only. Not applicable in normal operation!<br>I <sub>off</sub> > 0.5 mA  | ± 2.20   | kVDC         |  |                           |
|                            | Typical Off-State Current  | I <sub>off</sub>  | 0.8xV <sub>O</sub> , T <sub>case</sub> =25...70°C, reduced I <sub>off</sub> on request   | 10   | μADC         |  |                           |
|                            | Typical Turn-On Resistance   | R <sub>stat</sub>   | Each switching path<br>t <sub>p</sub> < 1μs, duty cycle < 1%<br>0.1 x I <sub>P(max)</sub> , T <sub>case</sub> =25°C<br>1.0 x I <sub>P(max)</sub> , T <sub>case</sub> =25°C<br>1.0 x I <sub>P(max)</sub> , T <sub>case</sub> =70°C                    | 1.70<br>3.59<br>7.40   | Ohm          |  |                           |
|                            | Typical Capacitive Power Dissipation of Switch (Natural Power Dissipation)   | P <sub>dc</sub>   | Switch capacitances only-<br>without external load and<br>parasitic capacitances!<br>0.8 x V <sub>O(max)</sub> , f = 10Hz<br>0.8 x V <sub>O(max)</sub> , f = 100Hz<br>0.8 x V <sub>O(max)</sub> , f = 10000Hz  | 0.01<br>0.10<br>1.28   | Watt         |  |                           |
|                            | Typical Propagation Delay Time   | t <sub>d(on)</sub>  | Resistive load, 0.1 x I <sub>P(max)</sub> , 0.8 x V <sub>O(max)</sub> , 50-50%   | 200  | ns           |  |                           |
|                            | Typical Output Pulse Jitter  | t <sub>j</sub>  | Impedance matched input, V <sub>aux</sub> / V <sub>ctrl</sub> = 5.00 VDC   | 2  | ns           |  |                           |
|                            | Typical Output Transition Time (Rise Time & Fall Time)   | t <sub>r</sub> , t <sub>f</sub>   | Resistive load, 10-90%<br>0.1 x V <sub>O(max)</sub> , I <sub>L</sub> = 0.1 x I <sub>P(max)</sub><br>0.8 x V <sub>O(max)</sub> , I <sub>L</sub> = 0.1 x I <sub>P(max)</sub><br>0.8 x V <sub>O(max)</sub> , I <sub>L</sub> = 1.0 x I <sub>P(max)</sub> | 15<br>40<br>60   | ns           |  |                           |
|                            | Maximum Turn-On Time   | t <sub>on(max)</sub>  | No limitation  | ∞  | ns           |  |                           |
|                            | Minimum Turn-On Time   | t <sub>on(min)</sub>  | can be customized. Please consult factory  | 100  | ns           |  |                           |
|                            | Max. Continuous Switching Frequency  | f <sub>(max)</sub>  | @ V <sub>aux</sub> = 5.00 V<br>Sw. shutdown if<br>f <sub>(max)</sub> is exceeded<br>Standard devices without HFS option<br>Standard devices with HFS supply<br>Opt. HFS + sufficient cooling option  | 23<br>50<br>100  | kHz          |  |                           |
|                            | Maximum Burst Frequency  | f <sub>b(max)</sub>   | Use option HFB for >10 pulses within 20μs or less  | 1.5  | MHz          |  |                           |
|                            | Maximum Number of Pulses / Burst   | N <sub>(max)</sub>  | f <sub>b</sub> >500 kHz (1μs spacing). Switch shutdown if N <sub>(max)</sub> is exceeded.  | 10 (Use burst option HFB for >10 pulses)                             | Pulses       |  |                           |
|                            | Coupling Capacitance   | C <sub>C</sub>  | Switch against control side  | < 100  | pF           |  |                           |
|                            | Natural Capacitance  | C <sub>N</sub>  | Between switch poles, @ 0.8 x V <sub>O(max)</sub>  | < 20   | pF           |  |                           |
|                            | Control Voltage Range  | V <sub>ctrl</sub>   | The V <sub>ctrl</sub> has no impact on the output pulse shape.   | 3 ... 10   | VDC          |  |                           |
|                            | Auxiliary Supply Voltage Range   | V <sub>aux</sub>  | The +5 V supply is not required in the HFS mode.   | 4.5 ... 5.5  | VDC          |  |                           |
|                            | Typical Auxiliary Supply Current   | I <sub>aux</sub>  | V <sub>aux</sub> = 5.00 VDC, T <sub>case</sub> = 25°C.<br>Active current limitation above 1A.<br>0.01 x f <sub>(max)</sub><br>@ specified f <sub>(max)</sub>   | 200<br>500   | mADC         |  |                           |
|                            | Opt. HFS, Ext. Supply Voltage V1   | V <sub>HFS(V1)</sub>  | Stability ±3%, current consumption <0.4 mA/kHz @ 25°C  | 15   | VDC          |  |                           |
|                            | Opt. HFS, Ext. Supply Voltage V2   | V <sub>HFS(V2)</sub>  | Stability ±3%, current consumption <0.5 mA/kHz @ 25°C  | 87   | VDC          |  |                           |
|                            | Intrinsic Diode Forward Voltage  | V <sub>F</sub>  | T <sub>case</sub> = 25°C, I <sub>F</sub> = 0.3 x I <sub>P(max)</sub>   | < 80   | VDC          |  |                           |
|                            | Diode Reverse Recovery Time  | t <sub>rrc</sub>  | T <sub>case</sub> = 25°C, I <sub>F</sub> = 0.3 x I <sub>P(max)</sub> , di/dt = 100 A/μs  | < 40   | ns           |  |                           |
| HOUSING                    | Dimensions   | LxWxH   | Standard housing, without pigtails<br>Devices with options DLC   | 89 x 64 x 22<br>Please consult BEHLKE!                               | mm³          |  |                           |
|                            | Weight   |   | Standard housing<br>Devices with options DLC   | Please consult BEHLKE!   | g            |  |                           |
| FUNCTIONS                  | Control Signal Input   | Lemo Pin 1: TTL compatible (LS-C: With 100Ω termination). Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V for low jitter).   |  |  |              |  |                           |
|                            | Logic GND / 5V Return  | Lemo Shielding: The logic ground is internally connected with the safety earthing terminal (threaded inserts).  |  |  |              |  |                           |
|                            | 5V Auxiliary Supply  | Lemo Pin 4: The 5 V input is used for rep rates up to the specified max. frequency f <sub>(max)</sub> . Higher rep rates require option HFS.  |  |  |              |  |                           |
|                            | Fault Signal Output  | Lemo Pin 3: TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault.  |  |  |              |  |                           |
|                            | Inhibit Signal Input   | Lemo Pin 2: TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited.   |  |  |              |  |                           |
|                            | LED Indicators      |  Green: "Auxiliary power good, switch OFF".  Yellow: "Control signal received, switch ON".  Red: "Fault condition, switch OFF" |  |  |              |  |                           |
|                            | Temperature Protection Air Cooling   | Standard switches and switches with options FC, CF and GCF: Thermotrigger 75°C, response time < 60 s @ 3xPd(max), ΔT=25K (50 to 75°C).  |  |  |              |  |                           |
|                            | Temperature Protection DLC Cooling   | Switches with option DLC: 65°C, response time < 3 s @ 3xPd(max), ΔT=25K (40 to 65°C), coolant flow > 3l / min. Separate driver protection.  |  |  |              |  |                           |
| ORDERING                   | <b>HTS 21-06-GSM</b><br>Push-Pull Switch, 2 kV, 60 A<br><br>For further ordering options please refer to our on-line catalog, section C8.<br><a href="https://www.behlke.com/separations/separation_c8.htm">https://www.behlke.com/separations/separation_c8.htm</a><br><br><b>BEHLKE</b><br>HIGH-TECH IN HIGH VOLTAGE |   | Option LP  | Low Pass. Input filter for increased noise immunity.                 | Option FO-I  | Fibre Optics Input for the inhibit and PPC signal.                                   |                           |
|                            |  |   | Option HFB   | High Frequency Burst (improved capability by external capacitors).   | Option FO-F  | Fibre Optics Output for the fault signal.  |                           |
|                            |  |   | Option HFS   | High Frequency Switching (two auxiliary supply inputs V1 & V2).      | Option UL-94 | Flame retardant casting resin, UL94-V0   |                           |
|                            |  |   | Option S-TT  | Soft Transition Time decrease the rise and fall time by 20%          | Option I-    | Integrated Free-Wheeling Diode. In connection with inductive load only.              |                           |
|                            |  |   | Option Min-  | Individually increased "Min. On-Time" to avoid unwanted triggering.  | Option I-    | Integrated Freewheeling Diode Network. In connection with inductive load.            |                           |
|                            |  |   | Option Min-  | Individually increased "Min. Off-Time" to avoid unwanted triggering. | Option LC-   | Removeable Power Driver, DLC cooling, solid aluminum housing.                        |                           |
|                            |  |   | Option PPC   | Pulse Pause Control for pauses between pos. and neg. pulses.         | Option SEP-  | Separated control unit. Control unit with LED indicators in a separate housing.      |                           |
|                            |  |   | Option ISO-  | 80kV Isolation. Isolation Voltage increased to 80kV.                 | Option I-PC  | Integrated part components according to customer specification.                      |                           |
|                            |  |   | Option ISO-  | 120kV Isolation. Isolation Voltage increased to 120kV.               | Option PCC   | Pulser Configuration. Switch combined with custom specific parts.                    |                           |
|                            |  |   | Option ISO-  | 160kV Isolation. Isolation Voltage increased to 160kV.               | Option CF    | Copper Cooling Fins. P <sub>d(max)</sub> can be increased by the factor 3 to 10      |                           |
|                            |  |   | Option ISO-  | 200kV Isolation. Isolation Voltage increased to 200kV.               | Option GCF   | Grounded Cooling Flange. P <sub>d(max)</sub> can be increased by the factor 3 to 15  |                           |
|                            |  |   | Option FO-C  | Fibre Optics Input for the control input.                            | Option DLC   | Direct Liquid Cooling. P <sub>d(max)</sub> can be increased by the factor 100 to 200 |                           |
|                            | Customized switching units are available on request. All data and specifications subject to change without notice. Please visit <a href="http://www.behlke.com">www.behlke.com</a> for up-dates.   |   |  |  | 21-06-GSM    | Revision 18.08.2025  | ©2012 All rights reserved |