

|  | Specification  | Symbol  | Condition / Comment   | 301-15-GSM-SiC  | Unit  |  |
|--|--|---|---|---|---|--|
| ABSOLUTE MAXIMUM RATINGS   | Maximum Operating Voltage  | $V_{O(max)}$  | $I_{off} < 50 \mu ADC$ , $T_{case} = 70^{\circ}C$   | $\pm 30$  | kVDC  |  |
|  | Maximum Isolation Voltage  | $V_I$   | Between HV switch and control / GND, continuously   | $\pm 40$  | kVDC  |  |
|  | Max. Housing Insulation Voltage  | $V_{INS}$   | Between switch and housing surface, 3 minutes   | $\pm 50$  | kVDC  |  |
|  | Maximum Turn-On Peak Current   | $I_{P(max)}$  | $T_{case} = 25^{\circ}C$<br>$t_p < 200 \mu s$ , duty cycle $< 1\%$<br>$t_p < 1 ms$ , duty cycle $< 1\%$<br>$t_p < 10 ms$ , duty cycle $< 1\%$<br>$t_p < 100 ms$ , duty cycle $< 1\%$  | 150<br>90<br>29<br>15   | ADC   |  |
|  | Maximum Continuous Load Current  | $I_{L(max)}$  | $T_{case} = 25^{\circ}C$<br>Standard devices<br>Option CF, cooling fins<br>Devices with option DLC  | 1.26<br>3<br>16   | ADC   |  |
|  | Max. Continuous Power Dissipation  | $P_{d(max)}$  | $T_{case} = 25^{\circ}C$<br>Standard devices & FC, forced air 4 m/s<br>Devices with option DLC  | 35<br>3000  | Watt  |  |
|  | Linear Derating  |   | Above $25^{\circ}C$<br>Standard devices & FC, forced air 4 m/s<br>Devices with option DLC   | 0.69<br>89  | W/K   |  |
|  | Operating Temperature Range  | $T_O$   | Standard devices & options ILC, DLC   | -40...70 (60)   | $^{\circ}C$   |  |
|  | Storage Temperature Range  | $T_S$   | Switches with option ILC may require frost protection!  | -40...90  | $^{\circ}C$   |  |
|  | Max. Permissible Magnetic Field  | B   | Homogeneous steady-field, surrounding the whole switch  | 25  | mT  |  |
|  | Max. Auxiliary Voltage   | $V_{aux}$   | Built-in overvoltage limiter (replaceable)  | 5.5   | VDC   |  |
| ELECTRICAL CHARACTERISTICS   | Permissible Operating Voltage Range  | $V_O$   | Unipolar operation (one switch pole grounded or floated)<br>Bipolar operation (positive & negative voltage applied)   | 0... $\pm 30$<br>0... $\pm 15$                                      | kVDC  |  |
|  | Typical Breakdown Voltage  | $V_{br}$  | NOTE: $V_{br}$ is a test parameter for quality control purposes only. Not applicable in normal operation!<br>$I_{off} > 0.5 mA$   | $\pm 33$  | kVDC  |  |
|  | Typical Off-State Current  | $I_{off}$   | $0.8 \times V_O$ , $T_{case} = 25...70^{\circ}C$ , reduced $I_{off}$ on request   | 50  | $\mu ADC$   |  |
|  | Typical Turn-On Resistance   | $R_{stat}$  | Each switching path<br>$t_p < 1 \mu s$ , duty cycle $< 1\%$<br>$0.1 \times I_{P(max)}$ , $T_{case} = 25^{\circ}C$<br>$1.0 \times I_{P(max)}$ , $T_{case} = 25^{\circ}C$<br>$1.0 \times I_{P(max)}$ , $T_{case} = 70^{\circ}C$ | 1.2<br>2.7<br>4.6   | Ohm   |  |
|  | Typical Capacitive Power Dissipation of Switch (Natural Power Dissipation) | $P_{dc}$  | Switch capacitances only- without external load and parasitic capacitances!<br>$0.8 \times V_{O(max)}$ , $f = 10Hz$<br>$0.8 \times V_{O(max)}$ , $f = 100Hz$<br>$0.8 \times V_{O(max)}$ , $f = 10000Hz$                       | 0.002<br>0.038<br>0.32  | Watt  |  |
|  | Typical Propagation Delay Time   | $t_{d(on)}$   | Resistive load, $0.1 \times I_{P(max)}$ , $0.8 \times V_{O(max)}$ , 50-50%  | TBD   | ns  |  |
|  | Typical Output Pulse Jitter  | $t_j$   | Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$  | 2   | ns  |  |
|  | Typical Output Transition Time (Rise Time & Fall Time)                     | $t_r, t_f$  | Resistive load, 10-90%<br>$0.1 \times V_{O(max)}$ , $I_L = 0.1 \times I_{P(max)}$<br>$0.8 \times V_{O(max)}$ , $I_L = 0.1 \times I_{P(max)}$<br>$0.8 \times V_{O(max)}$ , $I_L = 1.0 \times I_{P(max)}$                       | 30<br>50<br>60  | ns  |  |
|  | Maximum Turn-On Time   | $t_{on(max)}$   | No limitation   | $\infty$  | ns  |  |
|  | Minimum Turn-On Time   | $t_{on(min)}$   | can be customized. Please consult factory   | 180   | ns  |  |
|  | Max. Continuous Switching Frequency  | $f_{(max)}$   | @ $V_{aux} = 5.00 V$<br>Sw. shutdown if $f_{(max)}$ is exceeded<br>Standard devices without HFS option<br>Standard devices with HFS supply<br>Opt. HFS + sufficient cooling option  | 5.5<br>30<br>80   | kHz   |  |
|  | Maximum Burst Frequency  | $f_{b(max)}$  | Use option HFB for $> 10$ pulses within 20 $\mu s$ or less  | 500   | kHz   |  |
|  | Maximum Number of Pulses / Burst   | $N_{(max)}$   | $f_b = 1MHz$ (1 $\mu s$ spacing). Switch shutdown if $N_{(max)}$ is exceeded.   | 10  | Pulses  |  |
|  | Coupling Capacitance   | $C_C$   | Switch against control side<br>Standard devices & options CF, DLC   | $< 150$   | pF  |  |
|  | Natural Capacitance  | $C_N$   | Between switch poles, @ $0.5 \times V_{O(max)}$   | $< 20$  | pF  |  |
|  | Control Voltage Range  | $V_{ctrl}$  | The $V_{ctrl}$ has no impact on the output pulse shape.   | 3 ... 10  | VDC   |  |
|  | Auxiliary Supply Voltage Range   | $V_{aux}$   | The +5 V supply is not required in the HFS mode.  | 4.5 ... 5.5   | VDC   |  |
|  | Typical Auxiliary Supply Current   | $I_{aux}$   | $V_{aux} = 5.00 VDC$ , $T_{case} = 25^{\circ}C$ .<br>Active current limitation above 1A.<br>$0.01 \times f_{(max)}$<br>@ specified $f_{(max)}$  | 170<br>400  | mADC  |  |
|  | Opt. HFS, Ext. Supply Voltage V1   | $V_{HFS(V1)}$   | Stability $\pm 3\%$ , current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$  | 15  | VDC   |  |
|  | Opt. HFS, Ext. Supply Voltage V2   | $V_{HFS(V2)}$   | Stability $\pm 3\%$ , current consumption $< 0.5 mA/kHz$ @ $25^{\circ}C$  | 117   | VDC   |  |
|  | Intrinsic Diode Forward Voltage  | $V_F$   | $T_{case} = 25^{\circ}C$ , $I_F = 0.3 \times I_{P(max)}$  | $< 80$  | VDC   |  |
|  | Diode Reverse Recovery Time  | $t_{rr}$  | $T_{case} = 25^{\circ}C$ , $I_F = 0.3 \times I_{P(max)}$ , $di/dt = 100 A/\mu s$  | $< 40$  | ns  |  |
| HOUSING  | Dimensions   | $L \times W \times H$   | Standard housing, without pigtails<br>Devices with option ILC & DLC   | Please contact the manufacturer!                                    | mm <sup>3</sup>   |  |
|  | Weight   |   | Standard housing<br>Devices with option ILC & DLC   | Please contact the manufacturer!                                    | g   |  |
| FUNCTIONS  | Control Signal Input   | Pin 1 / Yellow (LS-C: Pin 1). TTL compatible (LS-C: With 100 $\Omega$ termination). Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V for low jitter).   |   |   |   |  |
|  | Logic GND / 5V Return  | Pin 2 / Black (LS-C: Shielding). The ground pin is internally connected with the safety earthings terminals (threaded inserts) on bottom side.  |   |   |   |  |
| ORDERING   | 5V Auxiliary Supply  | Pin 3 / Red (LS-C: Pin 4). The 5 V input is used for rep rates up to the specified max. frequency $f_{(max)}$ . Higher rep rates require option HFS.  |   |   |   |  |
|  | Fault Signal Output  | Pin 4 / Orange (LS-C: Pin 3). TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault.  |   |   |   |  |
|  | Inhibit Signal Input   | Pin 5 / Green (LS-C: Pin 2). TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited.  |   |   |   |  |
|  | LED Indicators   | GREEN: "Auxiliary power good, switch OFF". YELLOW: "Control signal received, switch ON". RED: "Fault condition, switch OFF"   |   |   |   |  |
|  | Temperature Protection   | A) Standard switches and switches with opt. FC, CF, GCF: Thermo trigger 75 $^{\circ}C$ , response time $< 60 s$ @ 3xPd(max), $\Delta T = 25K$ (50 to 75 $^{\circ}C$ ). Separate driver protection. B) Switches with option DLC: 65 $^{\circ}C$ , response time $< 3 s$ @ 3xPd(max), $\Delta T = 25K$ (40 to 65 $^{\circ}C$ ), coolant flow $> 3l / min$ . Separate driver protection. |   |   |   |  |
|  | HTS 301-15-GSM-SiC   | Fast HV Push-Pull Switch, 30kV, 150   | Option LP   | Low Pass. Input filter for increased noise immunity.                | Option I-PC   | Integrated part components according to customer specification.                          |
|  |  |   | Option HFB  | High Frequency Burst (improved capability by external capacitors)   | Option UL-94  | Flame retardant casting resin, UL94-V0   |
|  |  |   | Option HFS  | High Frequency Switching (two auxiliary supply inputs V1 & V2)      | Option I-FWD  | Integrated Free-Wheeling Diode. In connection with inductive load only.                  |
|  |  |   | Option I-HFS  | Integrated High Frequency Burst                                     | Option I-FWDN   | Integrated Freewheeling Diode Network. In connection with inductive load.                |
|  |  |   | Option S-TT   | Soft Transition Time decrease the rise and fall time by 20%         | Option PT-C   | Pigtail for control connection: Flexible leads (l=75mm) with lermo connector.            |
|  |  |   | Option Min-On   | Individually increased "Min. On-Time" to avoid unwanted triggering  | Option SEP-C  | Separated control unit. Control unit with LED indicators in a separate                   |
|  |  |   | Option Min-Off  | Individually increased "Min. Off-Time" to avoid unwanted triggering | Option TH   | Tubular Housing  |
|  |  |   | Option PCC  | Pulser Configuration. Switch combined with custom specific parts.   | Option CF   | Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.                |
|  |  |   | Option ISO-80   | 80kV Isolation. Isolation Voltage increased to 80kV.                | Option GCF  | Grounded Cooling Flange. $P_{d(max)}$ can be increased by the factor 3 to 15.            |
|  |  |   | Option ISO-120  | 120kV Isolation. Isolation Voltage increased to 120kV.              | Option ILC  | Indirect Liquid Cooling (for water). $P_{d(max)}$ can be increased by the factor 3 to 15 |
|  |  |   | Option ISO-160  | 160kV Isolation. Isolation Voltage increased to 160kV.              | Option DLC  | Direct Liquid Cooling. $P_{d(max)}$ can be increased by the factor 10 to 100.            |
|  |  |   | Option ISO-200  | 200kV Isolation. Isolation Voltage increased to 200kV.              | FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE. |  |
| Customized switching units are available on request. All data and specifications subject to change without notice. Please visit <a href="http://www.behlke.com">www.behlke.com</a> for up-dates. 301-15-GSM-SiC / Revision 12.11.2019 ©2012 All rights |  |   |   |   |   |  |