

	Specification	Symbol	Condition / Comment	HTS 31-03 AC-C	HTS 61-03-AC-C	Unit	
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	$V_{O(max)}$	$I_{off} < 50 \mu ADC$, $T_{case} = 70^{\circ}C$		3	6	kVDC
	Maximum Isolation Voltage	V_i	Between HV switch and control / GND, continuously		± 40		kVDC
	Max. Housing Insulation Voltage	V_{INS}	Between switch and housing surface, 3 minutes		± 40		kVDC
	Maximum Turn-On Peak Current	$I_{P(max)}$	$T_{case} = 25^{\circ}C$ $t_p < 200 \mu s$, duty cycle $< 1\%$ $t_p < 1 ms$, duty cycle $< 1\%$ $t_p < 10 ms$, duty cycle $< 1\%$ $t_p < 100 ms$, duty cycle $< 1\%$	30 19.5 12.6 8.1		ADC	
	Maximum Continuous Load Current	$I_{L(max)}$	$T_{case} = 25^{\circ}C$ Standard devices Devices with option DLC	0.6 3		ADC	
	Max. Continuous Power Dissipation	$P_{d(max)}$	$T_{case} = 25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	5 300	10 300	Watt	
	Linear Derating		Above $25^{\circ}C$ Standard devices & FC, forced air 4 m/s Devices with option DLC	0.11 4	0.22 8.5	W/K	
	Operating Temperature Range	T_o	Standard devices & options CF, GCF, ILC. (Option DLC)		-40...75		$^{\circ}C$
	Storage Temperature Range	T_s	Switches with option ILC may require frost protection!		-50...90		$^{\circ}C$
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch		25		mT
Max. Auxiliary Voltage	V_{aux}	Built-in overvoltage limiter (replaceable)		5		VDC	
ELECTRICAL CHARACTERISTICS	Permissible Operating Voltage Range	V_o			0... ± 3	0... ± 6	kVDC
	Typical Breakdown Voltage	V_{br}	NOTE: V_{br} is a test parameter for quality control purposes only. Not applicable in $I_{off} > 0.5 mA$	3.2	6.3	kVDC	
	Typical Off-State Current	I_{off}	$0.8 \times V_o$, $T_{case} = 25...70^{\circ}C$, reduced I_{off} on request		< 10		μADC
	Typical Turn-On Resistance	R_{stat}	Each switching path $t_p < 1 \mu s$, duty cycle $< 1\%$	$0.1 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 25^{\circ}C$ $1.0 \times I_{P(max)}$, $T_{case} = 70^{\circ}C$	10 21.3 63.4	20 42.6 40.6	Ohm
	Typical Propagation Delay Time	$t_{d(on)}$	Resistive load, $0.1 \times I_{P(max)}$, $0.8 \times V_{O(max)}$, 50-50%		100		ns
	Typical Output Pulse Jitter	t_j	Impedance matched input, $V_{aux} / V_{ctrl} = 5.00 VDC$		< 500		ns
	Typical Turn-On Rise Time	$t_{r(on)}$	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	TBD TBD TBD		ns
	Typical Turn-Off Rise Time	t_{off}, t_q	Resistive load, 10-90%	$0.1 \times V_{O(max)}$, $I_L = 0.1 \times I_{P(max)}$ $0.8 \times V_{O(max)}$, $I_L = 1.0 \times I_{P(max)}$	10 20		ns
	Maximum Turn-On Time	$t_{on(max)}$	No limitation		∞		
	Minimum Turn-On Time	$t_{on(min)}$	$t_{on(min)}$ can be customized. Please consult factory		100		ns
	Maximum Turn-Off Time	$t_{off(max)}$	No limitation		∞		
	Minimum Turn-Off Time	$t_{off(min)}$	$t_{off(min)}$ can be customized. Please consult factory		110		ns
	Max. Continuous Switching Frequency	f_{max}	@ $V_{aux} = 5.00 V$ Sw. shutdown if f_{max} is exceeded	Standard devices without HFS option Standard devices with HFS supply Opt. HFS + sufficient cooling option	TBD 80 150		kHz
	Maximum Burst Frequency	$f_{b(max)}$	Use option HFB for > 10 pulses within 20 μs or less		500		kHz
	Maximum Number of Pulses / Burst	$N_{(max)}$	@ $f_{b(max)}$ Note: Option HFB requires external buffer capacitors with a voltage rating of $> 630VDC$ and a capacitance of 100nF per additional	Standard Option I-HFB Option HFB	10 > 100 > 1000	Use option HFB for > 10	Pulses
	Coupling Capacitance	C_C	HV side against control side		12	10	pF
	Natural Capacitance	C_N	Between switch poles, @ $0.5 \times V_{O(max)}$		< 5		pF
	Control Voltage Range	V_{ctrl}	The V_{ctrl} has no impact on the output pulse shape.		2... 6		VDC
	Auxiliary Supply Voltage Range	V_{aux}	The +5 V supply is not required in the HFS mode.		5		VDC
	Typical Auxiliary Supply Current	I_{aux}	$V_{aux} = 5.00 VDC$, $T_{case} = 25^{\circ}C$. Active current limitation above 1A.	$0.01 \times f_{(max)}$ @ $f_{(max)}$	TBD 400	TBD 400	mADC
	Fault Signal Output		Switch will be turn off, if $f > f_{(max)}$, $V_{aux} < 4.75V$ or $T_{case} > 75^{\circ}C$ Fault condition is indicated by a logical "L"		H=4V, L=0.5V		VDC
	Opt. HFS, Ext. Supply Voltage V1	$V_{HFS(V1)}$	Stability $\pm 3\%$, current consumption $< 0.4 mA/kHz$ @ $25^{\circ}C$		15		VDC
	Opt. HFS, Ext. Supply Voltage V2	$V_{HFS(V2)}$	Stability $\pm 3\%$, current consumption $< 0.9 mA/kHz$ @ $25^{\circ}C$		TBD		VDC
	Intrinsic Diode Forward Voltage	V_F	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$		< 10		VDC
	Diode Reverse Recovery Time	t_{rrc}	$T_{case} = 25^{\circ}C$, $I_F = 0.3 \times I_{P(max)}$, $di/dt = 100 A/\mu s$		< 500		ns
	HOUSING	Dimensions	$L \times W \times H$	Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC	79x38x17 Please contact the manufactured!	125x38x17 Please contact the manufactured!	mm ³
Weight			Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC	Please contact the manufactured!		g	
FUNCTIONS	Control Signal Input	Pin 1 / Yellow. TTL compatible with Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V recommended for low jitter).					
	Logic GND / 5V Return	Pin 2 / Black. The ground pin is internally connected with the safety earthing terminal (threaded insert) on bottom side.					
	5V Auxiliary Supply	Pin 3 / Red. The 5 V input is used for rep rates up to the specified max. frequency f_{max} . Higher rep rates require option HFS.					
	Fault Signal Output	Pin 4 / Orange. TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault.					
	Inhibit Signal Input	Pin 5 / Green. TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited.					
	LED Indicators	GREEN: "Auxiliary power good, switch OFF". YELLOW: "Control signal received, switch ON". RED: "Fault condition, switch OFF"					
	Temperature Protection	A) Standard switches and switches with option CF, GCF: Thermo trigger $75^{\circ}C$, response time $< 60 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (50 to $75^{\circ}C$). Separate driver protection. B) Switches with option DLC: $65^{\circ}C$, response time $< 3 s$ @ $3 \times P_{d(max)}$, $\Delta T = 25K$ (40 to $65^{\circ}C$), coolant flow $> 3 l / min$. Separate driver protection.					
ORDERING TI	HTS 31-03	Transistor Switch, 3 kVDC, 30 ADC	Option LP	Low Pass. Input filter for increased noise immunity.	Option CCS	Ceramic Cooling Surface. $P_{d(max)}$ can be increased by the factor 2 to 3.	
	HTS 61-03	Transistor Switch, 6 kVDC, 30 ADC	Option S-TT	Soft Transition Time. Slower switching speed for simplified EMC.	Option CCF	Ceramic Flange Housing. $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option HFB	High Frequency Burst. Improved burst capability by driver.	Option CF	Copper Cooling Fins. $P_{d(max)}$ can be increased by the factor 3 to 10.	
			Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2)	Option GCF	Grounded Cooling Flange (copper). $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option UFTR	Ultra Fast Thermotrigger. Response time for shut down $< 5s$.	Option ILC	Indirect Liquid Cooling (for water). $P_{d(max)}$ can be increased by the factor 3 to 15.	
			Option UFTS	Ultra Fast Thermosensor. Response time $< 5s$. NTC 10k / $\pm 1\%$	Option DLC	Direct Liquid Cooling (for FPE/PFC). $P_{d(max)}$ can be increased by the factor 10 to 100. 15.	
FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE.							
Customized switching units are available on request. All data and specifications subject to change without notice. Please visit www.behlke.com for up-dates.				Revision 03-07-2018 ©2017 All rights reserved			