

Specification		Symbol	Condition / Comment		HTS 31-03-HB-AC-C		Unit	
ABSOLUTE MAXIMUM RATINGS	Maximum Operating Voltage	V <sub>O(max)</sub>	I <sub>off</sub> < 50 μADC, T <sub>case</sub> = 70°C		3		kVDC	
	Maximum Isolation Voltage	V <sub>I</sub>	Between HV switch and control / GND, continuously		± 10		kVDC	
	Max. Housing Insulation Voltage	V <sub>INS</sub>	Between switch and housing surface, 3 minutes		± 15		kVDC	
	Maximum Turn-On Peak Current	I <sub>P(max)</sub>	T <sub>case</sub> = 25°C	t <sub>p</sub> < 200 μs, duty cycle <1% t <sub>p</sub> < 1 ms, duty cycle <1% t <sub>p</sub> < 10 ms, duty cycle <1% t <sub>p</sub> < 100 ms, duty cycle <1%	30 19.5 12.6 8.1		ADC	
	Maximum Continuous Load Current	I <sub>L(max)</sub>	T <sub>case</sub> = 25°C	Standard devices Devices with option DLC	0.6 3		ADC	
	Max. Continuous Power Dissipation	P <sub>d(max)</sub>	T <sub>case</sub> = 25°C	Standard devices & FC, forced air 4 m/s Devices with option DLC	5 300		Watt	
	Linear Derating		Above 25°C	Standard devices & FC, forced air 4 m/s Devices with option DLC	0.11 4		W/K	
	Operating Temperature Range	T <sub>O</sub>	Standard devices & options CF, GCF, ILC. (Option DLC)		-40...75		°C	
	Storage Temperature Range	T <sub>S</sub>	Switches with option ILC may require frost protection!		-50...90		°C	
	Max. Permissible Magnetic Field	B	Homogeneous steady-field, surrounding the whole switch		25		mT	
Max. Auxiliary Voltage	V <sub>aux</sub>	Built-in overvoltage limiter (replaceable)		5		VDC		
ELECTRICAL CHARACTERISTICS	Permissible Operating Voltage Range	V <sub>O</sub>			0... ± 3		kVDC	
	Typical Breakdown Voltage	V <sub>br</sub>	NOTE: V <sub>br</sub> is a test parameter for quality control purposes only. Not applicable in I <sub>off</sub> > 0.5 mA		3.2		kVDC	
	Typical Off-State Current	I <sub>off</sub>	0.8xV <sub>O</sub> , T <sub>case</sub> =25...70°C, reduced I <sub>off</sub> on request		< 10		μADC	
	Typical Turn-On Resistance	R <sub>stat</sub>	Each switching path t <sub>p</sub> < 1μs, duty cycle < 1%	0.1 x I <sub>P(max)</sub> , T <sub>case</sub> =25°C 1.0 x I <sub>P(max)</sub> , T <sub>case</sub> =25°C 1.0 x I <sub>P(max)</sub> , T <sub>case</sub> =70°C	10 21.3 63.4		Ohm	
	Typical Propagation Delay Time	t <sub>d(on)</sub>	Resistive load, 0.1 x I <sub>P(max)</sub> , 0.8 x V <sub>O(max)</sub> , 50-50%		100		ns	
	Typical Output Pulse Jitter	t <sub>j</sub>	Impedance matched input, V <sub>aux</sub> / V <sub>ctrl</sub> = 5.00 VDC		<500		ns	
	Typical Turn-On Rise Time	t <sub>r(on)</sub>	Resistive load, 10-90%	0.1 x V <sub>O(max)</sub> , I <sub>L</sub> = 0.1 x I <sub>P(max)</sub> 0.8 x V <sub>O(max)</sub> , I <sub>L</sub> = 0.1 x I <sub>P(max)</sub> 0.8 x V <sub>O(max)</sub> , I <sub>L</sub> = 1.0 x I <sub>P(max)</sub>	TBD TBD TBD		ns	
	Typical Turn-Off Rise Time	t <sub>off</sub> , t <sub>q</sub>	Resistive load, 10-90%	0.1 x V <sub>O(max)</sub> , I <sub>L</sub> = 0.1 x I <sub>P(max)</sub> 0.8 x V <sub>O(max)</sub> , I <sub>L</sub> = 1.0 x I <sub>P(max)</sub>	10 20		ns	
	Maximum Turn-On Time	t <sub>on(max)</sub>	No limitation		∞			
	Minimum Turn-On Time	t <sub>on(min)</sub>	t <sub>on(min)</sub> can be customized. Please consult factory		70		ns	
	Max. Continuous Switching Frequency	f <sub>(max)</sub>	@ V <sub>aux</sub> = 5.00 V Sw. shutdown if f <sub>(max)</sub> is exceeded	Standard devices without HFS option Standard devices with HFS supply Opt. HFS + sufficient cooling option	TBD 80 150		kHz	
	Maximum Burst Frequency	f <sub>b(max)</sub>	Use option HFB for >10 pulses within 20μs or less		500		kHz	
	Maximum Number of Pulses / Burst	N <sub>(max)</sub>	@ f <sub>b(max)</sub> Note: Option HFB requires external buffer capacitors with a voltage rating of > 630VDC and a capacitance of 100nF per additional pulse	Standard Option I-HFB Option HFB	10 Use option HFB for >10 >100 >1000		Pulses	
	Coupling Capacitance	C <sub>C</sub>	HV side against control side		12		pF	
	Natural Capacitance	C <sub>N</sub>	Between switch poles, @ 0.5 x V <sub>O(max)</sub>		<5		pF	
	Control Voltage Range	V <sub>ctrl</sub>	The V <sub>ctrl</sub> has no impact on the output pulse shape.		2... 6		VDC	
	Auxiliary Supply Voltage Range	V <sub>aux</sub>	The +5 V supply is not required in the HFS mode.		5		VDC	
	Typical Auxiliary Supply Current	I <sub>aux</sub>	V <sub>aux</sub> = 5.00 VDC, T <sub>case</sub> = 25°C. Active current limitation above 1A.	0.01 x f <sub>(max)</sub> @ f <sub>(max)</sub>	TBD 400		mADC	
	Fault Signal Output		Switch will be turn off, if f>f <sub>(max)</sub> , V <sub>aux</sub> <4.75V or T <sub>case</sub> >75°C Fault condition is indicated by a logical "L"		H=4V, L=0.5V		VDC	
	Opt. HFS, Ext. Supply Voltage V1	V <sub>HFS(V1)</sub>	Stability ±3%, current consumption <0.4 mA/kHz @ 25°C		15		VDC	
	Opt. HFS, Ext. Supply Voltage V2	V <sub>HFS(V2)</sub>	Stability ±3%, current consumption <0.9 mA/kHz @ 25°C		TBD		VDC	
	Intrinsic Diode Forward Voltage	V <sub>F</sub>	T <sub>case</sub> = 25°C, I <sub>F</sub> = 0.3 x I <sub>P(max)</sub>		<10		VDC	
	Diode Reverse Recovery Time	t <sub>rrc</sub>	T <sub>case</sub> = 25°C, I <sub>F</sub> = 0.3 x I <sub>P(max)</sub> , di/dt = 100 A/μs		<500		ns	
	HOUSING	Dimensions	LxWxH	Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC		Please contact the manufactured!	Please contact the manufactured!	mm <sup>3</sup>
		Weight		Standard housing Devices with option CF, non-isolated cooling fins Devices with option DLC		Please contact the manufactured!		g
FUNCTIONS	Control Signal Input Logic GND / 5V Return	<b>Pin 1</b> / Yellow. TTL compatible with Schmitt-Trigger characteristics. Control voltage 2-10 V (3-5 V recommended for low jitter). <b>Pin 2</b> / Black. The ground pin is internally connected with the safety earthing terminal (threaded insert) on bottom side. <b>Pin 3</b> / Red. The 5 V input is used for rep rates up to the specified max. frequency f <sub>(max)</sub> . Higher rep rates require option HFS. <b>Pin 4</b> / Orange. TTL output, short circuit proof. Indicating switch & driver over-heat, over-frequency, low auxiliary voltage. L = Fault. <b>Pin 5</b> / Green. TTL compatible, Schmitt-Trigger characteristics for the connection of external safety circuits. L = Switch Inhibited. <b>GREEN:</b> "Auxiliary power good, switch OFF". <b>YELLOW:</b> "Control signal received, switch ON". <b>RED:</b> "Fault condition, switch OFF" <b>A)</b> Standard switches and switches with option CF, GCF: Thermo trigger 75°C, response time < 60 s @ 3xPd(max), ΔT=25K (50 to 75°C). Separate driver protection. <b>B)</b> Switches with option DLC: 65°C, response time < 3 s @ 3xPd(max), ΔT=25K (40 to 65°C), coolant flow > 3l / min. Separate driver protection.						
	5V Auxiliary Supply Fault Signal Output Inhibit Signal Input LED Indicators Temperature Protection							
ORDERING TI	HTS 31-03 HB-AC-C	Transistor Switch, 3 kVDC, 30 ADC	Option LP	Low Pass. Input filter for increased noise immunity.		Option CCS	Ceramic Cooling Surface. P <sub>d(max)</sub> can be increased by the factor 2 to 3.	
			Option S-TT	Soft Transition Time. Slower switching speed for simplified EMC.		Option CCF	Ceramic Flange Housing. P <sub>d(max)</sub> can be increased by the factor 3 to 15.	
			Option HFB	High Frequency Burst, Improved burst capability by driver.		Option CF	Copper Cooling Fins. P <sub>d(max)</sub> can be increased by the factor 3 to 10.	
			Option HFS	High Frequency Switching (two auxiliary supply inputs V1 & V2 )		Option GCF	Grounded Cooling Flange (copper). P <sub>d(max)</sub> can be increased by the factor 3 to 15.	
			Option UFTR	Ultra Fast Thermotriiger. Response time for shut down < 5s.		Option ILC	Indirect Liquid Cooling (for water). P <sub>d(max)</sub> can be increased by the factor 3 to 15.	
			Option UFTS	Ultra Fast Thermosensor. Response time < 5s. NTC 10k / ± 1%		Option DLC	Direct Liquid Cooling (for FPE/PFC). P <sub>d(max)</sub> can be increased by the factor 10 to 100. 15.	
FOR FURTHER PRODUCT OPTIONS PLEASE REFER TO THE OPTIONS PAGE								